

PLUMBING NOTES

- 1.) ALL PLUMBING SHALL CONFORM TO THE STATE OF MAINE PLUMBING CODE
- 2.) THE PLUMBING PLAN IS GENERALLY SHOWN IN SITUATION LOCATIONS OF PIPING AND EQUIPMENT SHALL BE FULLY COORDINATED W/ ALL TRADES
- 3.) ALL PLUMBING FIXTURES SHALL HAVE SHUT-OFF VALVES FOR ALL HOT AND COLD WATER SUPPLIES
- 4.) DESIGN OF WATER SYSTEM IS BASED ON 80 PSI @ ENTRANCE
- 5.) SEE SECTION 5F OF PLUMBING CODE FOR CLEAN-OUT REQUIREMENTS
- 6.) INSULATE ALL HOT & COLD WATER LINES W/ 1/2" ARMAFLEX
- 7.) FURNISH AND INSTALL 1/2" C.W. TRAP PRIMER ON ALL INDIRECT WASTES
- 8.) ALL HANDICAPPED LAVATORIES SHALL HAVE WASTES HOT & COLD WATER LINES UNDER FIXTURE INSULATED
- 9.) ALL PIPING SHALL BE CONCEALED IN WALLS AND ABOVE CEILING WHERE PRACTICAL
- 10.) SLOPE ALL HORIZONTAL WASTE & STORM LINES @ 1/8" FOOT

PLUMBING SYMBOLS

- VENT PIPING
- WASTE PIPING
- S--- STORM DRAIN PIPING
- C--- COLD WATER PIPING
- H--- HOT WATER PIPING
- C.O. --- CLEAN-OUT
- F.D. --- FLOOR DRAIN
- H.W. --- HOT WATER HEATER
- P-1 --- PLUMBING FIXTURE NUMBER
- X --- SHUT-OFF VALVE
- W.H.A. --- WATER HAMMER ARRESTOR
- PRV --- PRESSURE RELIEF VALVE
- COIL --- CONTAMINATED OIL LINE
- F --- FUEL GAUGE LINE
- F.U. --- FIXTURE UNIT
- 4" V.T.R. --- 4" VENT THRU ROOF

PLUMBING FIXTURE SCHEDULE

NUMBER	DESCRIPTION	WATER		WASTE	VENT	REMARKS
		COLD	HOT			
P-1	WATER CLOSET	1 1/2"	---	3"	2"	HANDICAPPED
P-2	LAVATORY	1/2"	1/2"	1 1/2"	1 1/4"	HANDICAPPED
P-3	ELECTRIC WATER COOLER	1/2"	---	1 1/4"	1 1/4"	HANDICAPPED
P-4	WASH SINK	3/4"	3/4"	2"	1 1/2"	3 FAUCETS
P-5	EMERGENCY WASH SHOWER	1 1/4"	---	---	---	---
P-6	INTERIOR HOSE BIBB	1/2"	1/2"	---	---	---
P-7	INTERIOR HOSE BIBB	1/2"	1/2"	---	---	HOT/COLD WATER
P-8	FROST-PROOF HOSE BIBB	1/2"	---	---	---	---
P-9	SERVICE SINK	1/2"	1/2"	2"	1 1/2"	---

